



Request your free sample today!

800.581.4645 | www.reedsmetals.com

REPEL II is 43% lighter than regular REPEL and weighs just 20 lbs for a 10 square roll. It comes in 250 lineal feet, 48" wide rolls and features a 25 year warranty. Ease of handling and high coverage allows you to dry in your roofs much faster than with traditional felts.

Reed's Metals provides a line of advanced synthetic roofing underlayment's designed for metal roofs. REPEL II is an economical option to our current REPEL underlayment and can be used in similar applications as a replacement for conventional asphalt-based roofing felts. Like REPEL, it's constructed of a high-strength woven polypropylene fabric that is several times stronger than asphalt felt and incorporates a specially formulated anti-slip walking surface. REPEL II offers outstanding nail sealing ability and UV resistance and can be exposed for up to six months.

Feature	REPEL™	REPEL II™	
Material	100% Polypropylene	100% Polypropylene	
Weight Per Roll	35 lbs	20 lbs	
UV-Resistance	YES-Up to 6 months	YES - Up to 6 months	
Anti-Slip Surface	YES	YES	
Warranty	YES - 25 years	YES - 25 years	
Class A Fire Rating	YES	YES	
Pre-Printed Nailing Pattern	YES	YES	
Roll Length / Width	250 lineal ft. / 48 in.	250 lineal ft. / 48 in.	
Roll Coverage	10 squares	10 squares	
Roll Length/Width	250 lineal ft. / 48 in.	250 lineal feet / 48 in	Test Method
Water Transmission	Pass	Pass	ASTM D-4869
Tensile Strength Machine Direction Cross Direction	96 lbs 116 lbs	57 lbs 57 lbs	ASTM D-828
Tear Strength Machine Direction Cross Direction	58 lbs 77 lbs	36 lbs 36 lbs	ASTM D-4533
Pliability	Pass	Pass	ASTM D-226
Water Ponding	Pass	Pass	ASTM D-779
Miami-Dade NOA	No. 05-0224.02	Pending	

800.581.4645 | www.reedsmetals.com

